

**AMENDMENTS TO THE CLAIMS**

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Original) A method of using the Host Identity Protocol (HIP) to at least partially secure communications between a first host operating in a first network environment and a second, HIP-enabled, host operating in a second network environment, with a gateway node forming a gateway between the two environments, the method comprising:

associating an identifier with the first host, storing the identifier at the gateway node, and sending the identifier to the first host;

using the identifier as a source address in a subsequent session initiation message sent from the first host to the gateway node and having an indication that the destination of the message is the second host; and

using the stored identifier at the gateway node to negotiate a secure HIP connection to the second host.

2. (Currently Amended) The [[A]] method as claimed in claim 1, wherein the identifier is generated at the gateway node.

3. (Currently Amended) The [[A]] method as claimed in claim 2, wherein the identifier is generated in response to the sending of a context activation request from the first host to the gateway node.

4. (Currently Amended) The [[A]] method as claimed in claim 3, wherein the context activation request is a Packet Data Protocol (PDP) context activation request to activate a PDP context, and the identifier is used as the PDP address in the PDP context.

5. (Currently Amended) The ~~[[A]]~~ A method as claimed in claim 1 ~~any preceding claim~~, wherein the first host is not HIP enabled and the secure HIP connection is negotiated between the gateway node and the second host.

6. (Currently Amended) The ~~[[A]]~~ A method as claimed in claim 1 ~~any one of claims 1 to 4~~, wherein the first host is HIP enabled and the secure HIP connection is negotiated between the first and second hosts

7. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, wherein the identifier is of the same length as an address in the addressing scheme used by the first host for communication with the gateway node.

8. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 7, wherein the IP addressing scheme is used and the identifier is used as the source IP address in the session initiation message.

9. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, wherein the identifier is a look-up identifier associated with a HIP identity tag generated for and associated with the first host, allowing the HIP identity tag for the first host to be retrieved at the gateway node using the look-up identifier.

10. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any one of claims 1 to 8~~, wherein the identifier is a HIP identity tag.

11. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 9 ~~or 10~~, ~~when dependent on claim 5~~, wherein the HIP identity tag is included in a HIP header during negotiation of the HIP connection between the gateway and the second host.

12. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 9, ~~10 or 11~~, wherein the HIP identity tag is a Host Identity Tag (HIT) or a Local Scope Identifier (LSI).

13. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 9 ~~any one of claims 9 to 12~~, wherein the HIP identity tag is generated from a key pair.

14. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 13~~—when dependent on claim 5~~, wherein the key pair which is stored in the gateway node for use during subsequent HIP communications between the gateway node and the second host.

15. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any one of claims 1 to 9~~, wherein the identifier is in the form of an IP address.

16. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, wherein the first network environment is a mobile network environment.

17. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 16, wherein the mobile network environment is a 3G mobile environment.

18. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 17, wherein the mobile network environment is a UMTS mobile network environment.

19. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, wherein the second network environment is an Internet network environment.

20. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, wherein the gateway node provides the functionality of a HIP proxy.

21. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, wherein the gateway node is a Gateway GPRS Support Node (GGSN).

22. (Currently Amended) The ~~[[A]]~~ method as claimed in claim 1 ~~any preceding claim~~, comprising replacing the identifier with an address associated with the gateway node as the source address in a subsequent message sent to the second host.

23. (Currently Amended) A communications system comprising :

- a first host operating in a first network environment,
- a second, Host Identity Protocol (HIP) enabled, host operating in a second network environment,
- a gateway node forming a gateway between the two environments,
- means for associating an identifier with the first host,
- means for storing the identifier at the gateway node,
- means for sending the identifier to the first host,
- means for using the identifier as a source address in a subsequent session initiation message sent from the first host to the gateway node and having an indication that the destination of the message is the second host, and
- means for using the stored identifier at the gateway node to negotiate a secure HIP connection to the second host.

24. (Currently Amended) A method, for use by a gateway node, of using the Host Identity Protocol(HIP) to at least partially secure communications between a first host operating in a first network environment and a second, HIP-enabled, host operating in a second network environment, with the gateway node forming a gateway between the two environments, the method comprising:

- associating an identifier with the first host, storing the identifier at the gateway node, and sending the identifier to the first host;

receiving a subsequent session initiation message sent from the first host to the gateway node, the message having the identifier as a source address and also having an indication that the destination of the message is the second host; and

using the stored identifier at the gateway node to negotiate a secure HIP connection to the second host.

25. (Original) An apparatus for use as a gateway node between a first host operating in a first network environment and a second, Host Identity Protocol (HIP) enabled, host operating in a second network environment, comprising:

means for associating an identifier with the first host,

means for storing the identifier at the gateway node,

means for sending the identifier to the first host,

means for receiving a subsequent session initiation message sent from the first host to the gateway node, the message having the identifier as a source address and also having an indication that the destination of the message is the second host, and

means for using the stored identifier at the gateway node to negotiate a secure HIP connection to the second host.

26. – 30. (Canceled)